

MODLINK MSDD DATA INSERT

2×USB-A female/male 0,7m cable

USB; USB (form A)

2× USB (female/female/0.7 m cable) form A

[Link to Product](#)**Illustration**

Product may differ from Image

**Commercial data**

| | |
|-----------------------|---------------|
| ECLASS-6.0 | 27189217 |
| ECLASS-6.1 | 27189217 |
| ECLASS-7.0 | 27189217 |
| ECLASS-8.0 | 27189217 |
| ECLASS-9.0 | 27189217 |
| ECLASS-10.1 | 27182806 |
| ECLASS-11.1 | 27182806 |
| ECLASS-12.0 | 27182806 |
| ETIM-5.0 | EC002625 |
| customs tariff number | 85444290 |
| GTIN | 4048879037846 |
| Packaging unit | 1 |

Mechanical data | Mounting data

| | |
|--------|-------|
| Height | 88 mm |
| Width | 51 mm |
| Depth | 45 mm |

Environmental characteristics | Climatic

| | |
|--------------------------|--------|
| Storage temperature min. | -10 °C |
| Storage temperature max. | 60 °C |

USB

| | |
|----------------------|------|
| Operating voltage AC | 48 V |
|----------------------|------|

| | |
|----------------------------------|-------------------|
| Operating voltage DC | 48 V |
| Operating voltage DC (UL-listed) | 42,4 V |
| Operating current max. | 500 mA |
| USB specification | 2.0 |
| Data transmission rate max. | 480 MBit/s |
| Looking techniques | Snap-in connector |