

MVP12, 8XM12, 5POLE, BASIC HOUSING

Without cap, with potent. sep.


8-way, 5-pole  
Potential separation as option  
Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.  
Further cable lengths on request.

Link to Product

Illustration



Product may differ from Image



Commercial data	
ECLASS-6.0	27279219
ECLASS-6.1	27279219
ECLASS-7.0	27279219
ECLASS-8.0	27279219
ECLASS-9.0	27440108
ECLASS-10.1	27440111
ECLASS-11.1	27440111
ECLASS-12.0	27440111
ETIM-5.0	EC002585
customs tariff number	85369010
GTIN	4048879064118
Packaging unit	1
Electrical data   Supply	
Operating voltage DC	24 V
Current operating per contact max.	4 A
Total current at 1 time current feed-in max.	8 A
Total current at 2 times current feed-in max.	16 A
Industrial communication	

Number of signals per port 2

#### Installation | Connection

Mounting set M12 x 1

#### Device protection | Electrical

Degree of protection (EN IEC 60529) IP67

Additional condition protection degree screwed, mounted

#### Device protection | Media

Flame resistance flame retardant

#### Mechanical data | Material data

Material housing Plastic

#### Mechanical data | Mounting data

Mounting method Schraubgewinde

Height 149,2 mm

Width 50,2 mm

Depth 17,2 mm

#### Environmental characteristics | Climatic

Operating temperature min. -20 °C

Operating temperature max. 80 °C

#### Connection type 2

Family construction form Cap

No. of poles 21

Family construction form M12

Gender female

Color contact carrier black

Coding A

No. of poles 5

PIN 1 +

PIN 2 NC S 2

PIN 3 -

PIN 4 NO S 1

PIN 5 PE