MURR ELEKTRONIK
stay connected

M12 Power female 0° L-cod. IDC

5-pol., 0,75 - 1,5mm², 5,8 - 13,5mm, shielded

M12 (母头) 5芯, L-编码
现场接线
压接
0.75...1.5 mm²
夹接范围 (电缆直径)
5.8...13.5 mm
塑料外壳, 有较好的防油防化学腐蚀性能
耐化学腐蚀性能需相对相关应用进行测试. 更多信息需单独获取.

链接至具体产品

图示







产品可能与图示有所不同

Family construction form	M12P
编码	L
材料触头	铜质

商业信息

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104

ECLASS-9.0	27440102
ECLASS-10.1	27440102
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ETIM-5.0	EC001855
GTIN	4048879682558
包装单位	1
海关税号	85366990
电气数据 | 供电	
最大工作电压 DC	63 V
每个触点的最大工作电流	12 A
技术参数 | 安装	
最大连接横截面	1,5 mm²
安装 | 连接	
紧固扭矩	0,6 Nm
固定装置	M12 x 1
扳手开口宽度	SW17
最小配对周期	500
设备保护 | 电动	
防护类型（EN IEC 60529）	IP65, IP67
防护类型附加条件	插入, 用螺丝拧紧
技术参数 | 机械数据	
波纹软管轮廓	无
机械数据 | 材料数据	
外壳涂层	Nickeled
触点涂层	镀金
材料外壳	压铸锌
材质触头支架	PA
机械数据 | 安装日期	
安装方式	插入, 用螺丝拧紧, 振动保护
最小夹紧范围	5,8 mm
最大夹紧范围	13,5 mm
高度	53 mm
宽度	25 mm
深度	25 mm
环境特性 | 气候	
最小工作温度	-40 °C
最大工作温度	85 °C
Important installation notes	
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
Note on bending radius	**Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.

穆尔电子元器件（上海）有限公司 | 上海市普陀区绥德路628号C幢 | 200331 上海 | 电话 +86 21 6284 7607 | 传真 +86 21 6284 8526 | shop@murrelektronik.com.cn | shop.murrelektronik.com.cn